



The **OVATION** series is designed to guarantee superior performance. All speaker cabinets are internally braced to ensure a tighter base, while metal phase plugs help develop a clear and natural mid-range. Polyimide switches protect against tweeter failure and full magnetic shielding promotes ideal placement opportunities.

The **OV30** bookshelf convincingly plays front or rear position, relying on a single 5.25" woofer and a 1" silk dome tweeter. The **OV50** tower uses a two 6.5" rubber-suspended treated-paper woofers and mid-range driver, along with a 1" silk dome tweeter. Dual 4" woofers and a 1" silk dome tweeter bring focus and detail to create an exciting sound environment, while the **OVC** center channel produces natural and balanced tones.

The **OVATION OVSUB** is a beautifully crafted, 150 watt, 10" down-firing, down-ported subwoofer. Solid and convincing performance is rivaled only by its simple elegance.



OV50



OV30



METAL PHASE PLUG:
Ovation Speakers develop clear and natural mid-range tones using a speaker driver metal phase plug.



OVC



OV30



OVSUB

Available in Black, (add suffix 'N') and Cherry (add suffix 'Ch')

Model	System	Woofer mm / inches	Midrange mm / inches	Tweeter mm / inches	Suggested Amplifier	Frequency Response	Ohms	Sensitivity 1w / 1m	Volume Litres	Weight Kg / lbs	Dimensions (H x W x D) mm / inches
OV30	2-way BR	133 / 5.25	N/A	25 / 1	20 ~ 100 w	65 Hz ~ 20 kHz	6	87 dB	12.2	4.2 / 9.4	300 x 181 x 219 / 11.9 x 7.1 x 8.8
OV50	3-way BR	165 / 6.5	165 / 6.5	25 / 1	20 ~ 150 w	45 Hz ~ 20 kHz	6	88 dB	66.0	20.0 / 44	1019 x 203 x 321 / 40.1 x 8.0 x 12.6
OVC	2-way BR	2 x 102 / 2 x 4	N/A	25 / 1	20 ~ 100 w	80 Hz ~ 20 kHz	6	87 dB	13.5	5.4 / 12.0	152 x 422 x 219 / 6.0 x 16.6 x 8.6

Model	Power	Woofer mm/inches	Phase Switch	Impedance	Response	Auto On/Off Delay	Volume Litres	Weight Kg / lbs	Dimensions (H x W x D) mm / inches
OVSUB	150 w	250 / 10	0° or 180°	200 / 47k Ohm	40 Hz ~ 180 kHz	0.9 sec / 15 min	68.0	17.7 / 39.1	352 x 403 x 452 / 13.9 x 15.9 x 17.8