

Big Boom Subwoofers

Black

Subwoofers have become an integral part of all home theatre systems. They deliver the deep, rich bass frequencies essential for recreating big theater effects at home.

BIG BOOM subwoofers are also a wonderful complement to stereo speakers when enjoying your favorite music. Full bodied and musical, they will enhance your listening pleasure according to your own preferred sound and level settings.

BIG BOOM front-firing subwoofers feature many design and performance details. All models are constructed of thick non-resonant MDF panels to eliminate unwanted cabinet vibrations. Vented pole piece long-throw woofers with rubber suspension, together with rugged class A/B overdrive-protected amplifiers, provide increased durability and extended power handling capacity while lessening distortion. In addition, **BIG BOOM** down-firing bass reflex ports are equipped with port tubes flared at both ends to further reduce sound distortion, while delivering a full bass performance.



BBF-212

ESTHETICALLY PLEASING AND FUNCTIONAL:
The sloped front baffle of the **BIG BOOM** front-firing series helps to eliminate standing waves within the cabinet, a process essential to developing a clearer, fuller performance.



BBF-212



BBF-210V3



BBF-208



BBF-206

Available in Black

| Model | Power | Woofer mm / inches | Phase Switch | Impedance | Frequency Response | Auto On/Off Delay | Volume Litres | Weight Kg / lbs | Dimensions (H x W x D) mm / inches |
|------------|-------|--------------------|-----------------|---------------|--------------------|-------------------|---------------|-----------------|--------------------------------------|
| BBF-206 | 75 w | 165 / 6.5 | Yes (0° or 18°) | 200 / 47k Ohm | 38 Hz ~ 150 kHz | 0.9 sec. / 15 min | 30 | 7.7 / 17.0 | 342 x 209 x 419 / 13.5 x 8.3 x 16.5 |
| BBF-208 | 100 w | 210 / 8 | Yes (0° or 18°) | 200 / 47k Ohm | 34 Hz ~ 150 kHz | 0.9 sec. / 15 min | 51 | 13.0 / 27.8 | 381 x 279 x 476 / 15.0 x 11.0 x 18.8 |
| BBF-210 V3 | 150 w | 254 / 10 | Yes (0° or 18°) | 200 / 47k Ohm | 30 Hz ~ 150 kHz | 0.9 sec. / 15 min | 79 | 16.7 / 36.7 | 438 x 317 x 571 / 17.3 x 12.5 x 22.5 |
| BBF-212 | 200 w | 304 / 12 | Yes (0° or 18°) | 200 / 47k Ohm | 27 Hz ~ 150 kHz | 0.9 sec. / 15 min | 104 | 20.2 / 44.6 | 476 x 381 x 571 / 18.8 x 15.0 x 22.5 |

Big Boom Subwoofers

Subwoofers

OMAGE®

BBF-215

For serious bass enthusiasts, **OMAGE** presents the **BBF-215**. A front-firing, 15" rubber suspended sub with twin, low-noise rear ports, the **BBF-215** is equipped with a 300-watt RMS low-heat, high-efficiency amplifier. The dynamics of a powerful amplifier, a large woofer, a high temperature-tolerant voice coil and a full-sized cabinet ensure not only big-time performance, but also full and rich sound, even at lower listening ranges.

Black

CABINET:

The cabinet is constructed of 1" thick MDF to enhance sonic purity.

OVERLOAD PROTECTION:

The **BBF-215** design features both dynamic overdrive and over-heating protection.



BBF-215

BBD-10

The **BBD-10** is the smallest 10" subwoofer in the **Big Boom** series. Measuring only 13" cubed, it is a down-firing, front-ported, fully-featured active subwoofer. The **BBD-10** gives you great performance and more boom for your buck!



BBD-10 back panel



BBD-10



Big Boom amplifier control panel

FULL FEATURED AMPLIFIER:

BIG BOOM amplifiers include all important controls and connection options. Their substantial power promotes, clear and convincing performance.

Available in Black

| Model | Power | Woofer mm / inches | Phase Switch | Suggested Amplifier | Frequency Response | Auto On/Off Delay | Volume Litres | Weight Kg / lbs | Dimensions (H x W x D) mm / inches |
|---------|-------|-----------------------|-----------------|------------------------|-----------------------|----------------------|------------------|--------------------|---------------------------------------|
| BBD-10 | 70 w | 254 / 10 | Yes (0° or 18°) | 200 / 10k Ohm | 35 Hz ~ 150 kHz | 0.9 sec. / 15 min | 36 | 12.5 / 27.0 | 330 x 330 x 330 / 13.0 x 13.0 x 13.0 |
| BBF-215 | 300 w | 381 / 15 | Yes (0° or 18°) | 200 / 47k Ohm | 25 Hz ~ 150 kHz | 0.9 sec. / 25 min | 108 | 34.5 / 76.0 | 508 x 432 x 495 / 20.0 x 17.0 x 19.5 |